



11636 GOLDRING RD • ARCADIA, CALIFORNIA 91006-5815
626-358-2559 • FAX 626-359-5701 • 800-525-6925

Installation Instructions
Telephone Headset Patch with 15db Gain
THP-734SY P/N 43794

The THP-734SY provides an analog audio connection to recorders and loggers from telephones that have modular or dual pin connected handsets or headsets. It allows clear recording of both sides of your conversation with digital or analog phones. The audio output to the recorder is amplified 15db.

Installation:

1. Disconnect the handset/headset cord from the base of the telephone and replace it with the modular plug from the THP-734SY, or use the modular-to-dual pin adapter, 43174 included with the unit.
2. Connect the handset/headset cord into the modular receptacle or the dual pin jacks on the THP-734SY.
3. The audio output to the recorder is provided on the center pair (pins 3 & 4) of the RJ-11 modular jack on the back of the THP-734SY.
4. The unit is powered by a 6VDC plug-in AC Adapter, part # 39184, furnished with the unit. Insert the power cord into the power supply jack on the THP-734SY. Plug the adapter into any adjacent power outlet for 115 VAC power. The center contact of the power plug is negative DC polarity.

Installation Instructions

Telephone Headset Patch with 15db Gain

THP-734SY P/N 43794

